



Omega
The Ultimate Lubricant

5W30

DESCRIPTION:

Fully synthetic engine oil designed with the latest additives system which meets industry's highest API standards for gasoline engine so far. It is engineered to maximize engine life and give extraordinary fuel economy and protecting against wear under severe service conditions.

KEY BENEFITS:

- ❑ Excellent fuel economy and superior thermal stability enabling extra saving & long engine life.
- ❑ Outstanding high shear/high temperature performance reduces engine scuffing and bore polishing thus extend engine life.
- ❑ Minimize oil consumption under severe condition through viscosity retention.
- ❑ Excellent low temperature capabilities which enhances quick cold weather starting.

MEET THE REQUIREMENTS OF:

- ACEA C3-12
- MB 229.31/229.51
- MB 226.5
- API SN/CF
- BMW LONGLIFE – 04
- GM DEXOS 2
- PORSCHE A40
- RENAULT RN0700/0710

APPLICATIONS:

This oil is recommended for modern vehicles including high performance turbo-charged and super-charged passenger car, SUV and vans under the vehicles manufacturer's recommendation.

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
		SAE 5W30
Appearance	-	Amber
Viscosity, cSt @ 40°C	D-445	64.0
Viscosity, cSt @ 100°C	D-445	11.0
Viscosity Index	D-2270	162
Flash Point, COC, °C	D-92	≥ 200
Pour Point, °C	D-97	-39
Total Base Number, mg KOH/g	D-2896	7.9

The characteristics given above are typical of current production only and slight batch to batch variations should be expected.